

LED line LITE Code: 245954 EAN: 5901583245954

LED bulb G9 4000K 6W 550lm 230V 270° Ceramic LITE





LED bulb G9 6W 4000K 550lm from LED line LITE is an efficient light source, characterized by a light stream of 550 lumens and high efficiency of 92 lm/W. At 4000 K colour temperature, it emits neutral white light, ideal for a variety of interiors. Ra $\geq \! 80$ color reproduction factor provides excellent color rendering.









Technical data

Parameter	Value
Energy efficiency class 2019/2015	F
Energy class	A+
Warranty	3
Power	• 6 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
Luminous efficacy	92
Luminous flux	550 lm
The lumen maintenance factor	96
Lifetime L70B50	30 000 h
Survival factor	0.9

Parameter	Value
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
Fixture's diameter	16 mm
Beam angle	270 °
LED type	SMD2835
Power Factor	0,5
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Height	66
Colour	white
Material (housing)	Ceramics




LED line LITE Code: 245954 EAN: 5901583245954

LED bulb G9 4000K 6W 550lm 230V 270° Ceramic LITE

Technical drawing



Light distribution




Additional product photos






Logistics data






Single packaging

Quantity	1
Width	50 mm
Height	50 mm
Length	60 mm
Weight	0,02 kg



Bulk packaging

Quantity	500
Width	610 mm
Height	235 mm
Length	150 mm
Volume	0,021 m3
Weight	10,06 kg
Comments	



Europallet

Quantity	40000
Height	1,6 m
Quantity in layer	3000
Number of layers	13
Bulk quantity	80
Weight	1120 kg

MORE EFFICIENCY FOR THE LED WORLD



LED line LITE Code: 245954 EAN: 5901583245954

LED bulb G9 4000K 6W 550lm 230V 270° Ceramic LITE

Example application