

LED line PRIME Code: 217089 EAN: 5905378217089

ESTADIO 300W 5000K 40° 170lm/w **CRI80 PRIME**







Stadium ESTADIO 300W 5000K 40° 170lm/in CRI80 D:S PRIME by LED line PRIME is an advanced lighting solution with high performance. It is characterized by a light stream of 51000 lumens and an energy efficiency factor of 170 lm/W. The technology used provides excellent color reproduction (CRI 80), which translates into the naturalness of the illuminated space.

















Technical data

| Parameter | Value |
|---------------------------------------|----------------|
| Energy efficiency class 2019/2015 | В |
| Warranty | 5 |
| Power | • 300 W |
| Voltage | • 100-227 V AC |
| Correlated colour temperature | • 5000 K |
| Colour of the light | White |
| IP protection rating | IP66 |
| IK protection rating | 10 |
| IEC protection class | 1 |
| Luminous efficacy | 170 |
| Luminous flux | 51000 |
| The lumen maintenance factor | 96 |
| Lifetime L70B50 | 100 000 h |
| Colour consistency in McAdam ellipses | ≤6 |
| Frequency of the supply voltage | 50/60Hz |
| | |

| Parameter | Value |
|--|---------------|
| CRI colour rendering index | 80 |
| Beam angle | 40 |
| LED type | EMC5050 |
| LED quantity | 100 |
| Power Factor | 0,95 |
| Lamp's warm-up time to 60% | 0,5 |
| Ambient temperature suitable for operation | -40 / +45 |
| For indoor use | Outside |
| Length | 388 |
| Width | 305 |
| Height | 150 |
| Weight | 4500 |
| Material (housing) | Aluminium |
| Material (cover) | Polycarbonate |



LED line PRIME Code: 217089 EAN: 5905378217089

ESTADIO 300W 5000K 40° 170lm/w CRI80 PRIME

Technical drawing


Light distribution



Additional product photos




Logistics data







| Weight | 5 kg | |
|--------|------|--|



Bulk packaging





Europallet

5

MORE EFFICIENCY FOR THE LED WORLD



LED line PRIME Code: 217089 EAN: 5905378217089

ESTADIO 300W 5000K 40° 170lm/w CRI80 PRIME

Example application