

LED line PRIME Code: 477415 EAN: 5907777477415

LED line® downlight 30W 3000lm 4000K QUANTUM





LED line downlight 30W 3000lm 4000K QUANTUM is an innovative lighting setting from the LED line PRIME, providing high light performance of 3000 lm at 30 W. Neutral colour of light 4000 K favours visual comfort and realistic color reproduction (Ra $\geq\!85$). The construction made of aluminium and polycarbonate guarantees durability and aesthetics.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	F
Energy class	A+/F
Warranty	5
Power	• 30 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	85
IP protection rating	IP20
IK protection rating	03
IEC protection class	II
Luminous efficacy	100
Luminous flux	3000
The lumen maintenance factor	96
Lifetime L70B50	50 000 h
Survival factor	0.9
Colour consistency in McAdam ellipses	≤3
Output current	0,75

Parameter	Value
Wire length	150 mm
Fixture's diameter	170 mm
Beam angle	60
LED type	COB
LED quantity	1
Lifespan	50 000 h
Power Factor	0,9
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-5÷40
For indoor use	Inside
Installation method	recessed
Mounting hole diameter	155
Height	58
Weight	260
Colour	White
Material (housing)	Aluminium
Material (cover)	Polycarbonate




LED line PRIME Code: 477415 EAN: 5907777477415

LED line® downlight 30W 3000lm 4000K QUANTUM

Technical drawing


Light distribution



Additional product photos




Logistics data




Single packaging

Quantity	1
Width	70 mm
Height	195 mm
Length	175 mm
Weight	0,08 kg



Bulk packaging

Quantity	20
Width	395 mm
Height	380 mm
Length	520 mm
Volume	0,059 m3
Weight	11,8 kg
Comments	



Europallet

480
1580 mm
6
4
24
288 kg

MORE EFFICIENCY FOR THE LED WORLD



LED line PRIME Code: 477415 EAN: 5907777477415

LED line® downlight 30W 3000lm 4000K QUANTUM

Example application