

LED line LITE

Code: 228948

EAN: 5905378228948

Floodlight PHOTON S 3CCT (3/4/6,5K)
30W 3000lm 120° IP65 LITE PIR sensor



PHOTON S is a professional floodlight for buildings, halls, and open areas. The aluminum housing, tempered glass, and pressure equalization system ensure IP66 and IK08. Efficient LEDs 100 lm/W, tool-free installation, 3 light colors, a lumen output of 1,000–30,000 lm, and a PIR option guarantee savings and versatile applications.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	F
Warranty	3
Power	• 30 W
Voltage	• 185-265 V AC
Correlated colour temperature	• 3000 K • 4000 K • 6500 K
Colour of the light	CCT
Colour rendering index Ra	80
IP protection rating	IP65
IK protection rating	06
IEC protection class	I
Luminous efficacy	100
Luminous flux	3000
Lifetime L70B50	30 000 h

Parameter	Value
Wyniki tłumaczenia Functional description of the daylight sensor [LUX]	Min 10 lx - Max 2000 lx
Detecting Area (Radius)	2 - 8 m
Frequency of the supply voltage	50/60Hz
Beam angle	120°
LED type	2835 6V
Power Factor	>=0,9
Ambient temperature suitable for operation	-20÷45
Length	169 mm
Width	173 mm
Height	27 mm
Weight	0,44 kg
Material (housing)	Aluminium

LED line LITE


Code: 228948

EAN: 5905378228948

Floodlight PHOTON S 3CCT (3/4/6,5K)

30W 3000lm 120° IP65 LITE PIR sensor


Technical drawing



Light distribution


Additional product photos

Logistics data




Single packaging

Width	195 mm
Height	60 mm
Length	195 mm
Weight	0,53 kg



Bulk packaging

Quantity	20
Width	405 mm
Height	315 mm
Length	405 mm
Weight	10,6 kg



Europallet

Quantity	320
Height	1,7 m
Bulk quantity	16
Weight	200 kg

LED line LITE

Code: 228948

EAN: 5905378228948

Floodlight PHOTON S 3CCT (3/4/6,5K)
30W 3000lm 120° IP65 LITE PIR sensor

Example application