

LED line PRIME

Code: 202115-II

EAN: 5905378216983

**LED tube T8 G13 6500K 22W 3300lm
230V 270° 150cm Glass PRIME**



The LED line T8 LED line PRIME 22W is an excellent solution for demanding users. It emits bright white light with a color temperature of 6500 K and a luminous flux of 3300 lumens, providing effective lighting in any room. With a power supply of 220-240 V AC and a power of 22 W, it achieves high energy efficiency. The product's lifespan is up to 25,000 hours, and the luminous flux maintenance factor reaches up to 96%.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	D
Warranty	5
Power	• 22 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 6500 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
Luminous efficacy	150
Luminous flux	3300 lm
The lumen maintenance factor	96
Lifetime L70B50	25 000 h
Survival factor	0.9
Colour consistency in McAdam ellipses	≤6

Parameter	Value
Frequency of the supply voltage	50/60Hz
Lamp's type	T8
Beam angle	270 °
LED type	SMD2835
LED quantity	120
Lifespan	25 000 h
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1
For indoor use	Inside
Length	1500
Material	Glass
Material (housing)	Glass
Material (cover)	glass


LED line PRIME

Code: 202115-II

EAN: 5905378216983

**LED tube T8 G13 6500K 22W 3300lm
230V 270° 150cm Glass PRIME**

Technical drawing



Light distribution

Additional product photos



Logistics data



Single packaging

Quantity	1
Width	47 mm
Height	14 mm
Length	47 mm
Weight	0,24 kg



Bulk packaging

Quantity	25
Width	1590 mm
Height	175 mm
Length	170 mm
Volume	0,047 m3
Weight	8,4 kg



Europallet

Height	1590 mm
Quantity in layer	600
Number of layers	1
Bulk quantity	600
Weight	101 kg

LED line PRIME

Code: 202115-II

EAN: 5905378216983

**LED tube T8 G13 6500K 22W 3300lm
230V 270° 150cm Glass PRIME**

Example application