

LED line PRIME


Code: 475725

EAN: 5907777475725

LED line PRIME FUSION linear lamp
20W 4000K 2600lm 0-10V P18° black



The linear FUSION 20W from the PRIME LED line provides light performance of 130 lm/W and a total light stream of 2600 lm at 4000 K colour temperature, resulting in natural and pleasant lighting. Its assembly is simple thanks to the universal shape, which allows a variety of installation methods. Made of aluminium, the luminaire guarantees excellent heat discharge and long-term operation of up to 50,000 hours.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	C
Warranty	5
Power	• 20 W
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IK protection rating	08
IEC protection class	I
Luminous efficacy	130
Luminous flux	2600
The lumen maintenance factor	96
Lifetime L70B50	50 000 h
Survival factor	0.9

Parameter	Value
Dimmable function	0-10
Colour consistency in McAdam ellipses	≤6
Sling length	200 cm
Standby power	ReplByProf2+ReplByProf3
Mounting type	mixed
Frequency of the supply voltage	50/60Hz
Power Factor	0,9
Lamp's warm-up time to 60%	1 s
Ambient temperature suitable for operation	-20÷45
For indoor use	Inside
Length	586
Width	70
Height	52

LED line PRIME

Code: 475725


EAN: 5907777475725

LED line PRIME FUSION linear lamp
20W 4000K 2600lm 0-10V P18° black

Technical drawing




Light distribution



Additional product photos




Logistics data




Single packaging

Width	586 mm
Height	52 mm
Length	70 mm
Weight	1,14 kg



Bulk packaging

Quantity	12
Width	690 mm
Height	260 mm
Length	260 mm
Volume	0,046 m3
Weight	13,93 kg
Comments	



Europallet

Quantity	288
Height	1710 mm
Quantity in layer	48
Number of layers	6
Bulk quantity	288
Weight	672 kg

LED line PRIME

Code: 475725

EAN: 5907777475725

**LED line PRIME FUSION linear lamp
20W 4000K 2600lm 0-10V P18° black**

Example application