

LED line LITE Code: 206755 EAN: 5905378206755

LED line LITE HighBay luminaire STREAKBAY 100W 4000K 10000lm





HighBay STREAKBAY from a 100W LED line LITE and a 10,000 lm light stream is a perfect solution for demanding industrial environments. It is characterized by colour temperature 4000K, which provides natural color reproduction. Its construction from aluminium casting in IP65 protection class guarantees resistance to difficult weather conditions.















Technical data

Parameter	Value
Energy efficiency class 2019/2015	E
Warranty	5
Power	• 100 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IK protection rating	08
IEC protection class	1
Luminous efficacy	100
Luminous flux	10000
The lumen maintenance factor	96
Lifetime L70B50	36 000 h
Survival factor	0.9


Parameter	Value
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
Beam angle	120x60
LED type	SMD LED
LED quantity	108
Power Factor	0,95
Lamp's warm-up time to 60%	1s
Ambient temperature suitable for operation	-40÷40
Length	545
Width	118
Height	78
Weight	1400
Material (housing)	Die cast aluminium
Material (cover)	polycarbonate



LED line LITE Code: 206755 EAN: 5905378206755


LED line LITE HighBay luminaire STREAKBAY 100W 4000K 10000lm

Technical drawing



Light distribution

Luminous [cd/klm]



Additional product photos












Logistics data







Single packaging

Quantity	1
Width	545 mm
Height	78 mm
Length	118 mm
Weight	1,42 kg

Bulk packaging

Quantity	5
Width	485 mm
Height	145 mm
Length	565 mm
Volume	0,039 m3
Weight	8,7 kg

Europallet

Height	1885 mm
Quantity in layer	10
Number of layers	13
Bulk quantity	130
Weight	226,2 kg

MORE EFFICIENCY FOR THE LED WORLD



LED line LITE Code: 206755 EAN: 5905378206755

LED line LITE HighBay luminaire STREAKBAY 100W 4000K 10000lm

Example application