

LED line LITE

Code: 203303

EAN: 5905378203303

**LUMINO Floodlight 4000K 30W 3000lm  
120° IP65 LITE**



LUMINO 30W LED line LITE is an advanced and efficient light source, offering a light stream of 3,000 lumens at a colour temperature of 4000 K. Its excellent performance is as much as 100 lm/W, which allows significant energy savings. Thanks to the IP65 seal class, it is resistant to water and dust, which confirms its application in difficult conditions.



**Technical data**

Parameter	Value
Energy efficiency class 2019/2015	F
Warranty	3
Power	• 30 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	70
IP protection rating	IP65
IK protection rating	05
IEC protection class	I
Luminous efficacy	100
Luminous flux	3000
The lumen maintenance factor	96
Lifetime L70B50	25 000 h
Survival factor	0.9

Parameter	Value
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
Beam angle	110
LED type	SMD LED
LED quantity	28
Power Factor	0,9
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Length	139
Width	164
Height	29
Weight	350
Material (housing)	Die cast aluminium
Material (cover)	Tempered glass


LED line LITE

Code: 203303


EAN: 5905378203303

**LUMINO Floodlight 4000K 30W 3000lm  
120° IP65 LITE**

**Technical drawing**






**Light distribution**



**Additional product photos**



**Logistics data**



**Single packaging**

Quantity	1
Width	139 mm
Height	29 mm
Length	164 mm
Weight	0,32 kg

**Bulk packaging**

Quantity	20
Width	310 mm
Height	195 mm
Length	360 mm
Volume	0,021 m3
Weight	6,75 kg

**Europallet**

Height	1950 mm
Quantity in layer	240
Number of layers	6
Bulk quantity	1440
Weight	486 kg

---

LED line LITE

Code: 203303

EAN: 5905378203303

**LUMINO Floodlight 4000K 30W 3000lm  
120° IP65 LITE**

---

**Example application**