

LED line LITE

Code: 247798

EAN: 5901583247798

LED bulb MR16 4000K 3W 273lm 10-14V
AC/DC 36° GU5,3 Glass LITE



LED bulb MR16 3W 4000K from LED line LITE is an energy-efficient light source that emits a bright, white light with a luminous flux of 273 lumens. The SMD2835 technology used and Ra ≥80 colour reproduction factor ensure high quality and faithful color rendering. The product is adapted to a voltage of 10-14 V AC/DC and is characterized by a light angle of 36°, which allows precise lighting of selected areas.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	F
Energy class	A++
Warranty	3
Power	• 3 W
Voltage	• 10-14 V AC/DC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
Luminous efficacy	91
Luminous flux	273 lm
The lumen maintenance factor	96
Lifetime L70B50	30 000 h
Survival factor	0.9

Parameter	Value
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
Fixture's diameter	50 mm
Beam angle	36°
LED type	SMD2835
Power Factor	0,4
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Height	50
Material (housing)	Glass


LED line LITE

Code: 247798


EAN: 5901583247798

LED bulb MR16 4000K 3W 273lm 10-14V
AC/DC 36° GU5,3 Glass LITE

Technical drawing




Light distribution




Additional product photos

Logistics data




Single packaging

Quantity	10
Width	60 mm
Height	125 mm
Length	60 mm
Weight	0,06 kg



Bulk packaging

Quantity	100
Width	290 mm
Height	170 mm
Length	595 mm
Volume	0,029 m3
Weight	6,5 kg
Comments	



Europallet

Quantity	4500
Height	1870 mm
Quantity in layer	400
Number of layers	11
Bulk quantity	4400
Weight	286 kg

LED line LITE

Code: 247798

EAN: 5901583247798

**LED bulb MR16 4000K 3W 273lm 10-14V
AC/DC 36° GU5,3 Glass LITE**

Example application