

LED line PRIME Code: 241314 EAN: 5901583241314

# LED line downlight aluminium round gold/white OLTIKA



The LED line OLTIKA ceiling housing in an elegant white and gold finish combines aesthetics with functionality. Made of high quality aluminium casting, it has a diameter of 100 mm and IP20 leak class, which allows it to be used inside buildings. With a maximum power of 35W and the ability to adjust the direction of illumination, it provides optimal lighting. Easy installation in a 75 mm hole allows for quick installation of fittings in different interiors.









#### **Technical data**

Parameter	Value
Warranty	5
IP protection rating	IP20
IEC protection class	III
Maximum suitable lamp power	35 W
Fixture's diameter	100
Lamp's diameter	50 mm
Type of surface suitable for installation	F


Parameter	Value
Distance from illuminated surface	0.5 m
Installation method	recessed
Mounting hole diameter	75
Height	40
Colour	gold & white
Material (housing)	Die cast aluminium



LED line PRIME Code: 241314 EAN: 5901583241314

## LED line downlight aluminium round gold/white OLTIKA


#### **Technical drawing**




#### **Light distribution**

#### Additional product photos


#### Logistics data






#### Single packaging

Width	100 mm
Height	40 mm
Length	100 mm
Weight	0.07 kg



#### **Bulk packaging**

Quantity	100
Width	0 mm
Height	0 mm
Length	1000 mm
Volume	0 m3
Weight	9,4 kg
Comments	



#### **Europallet**

Quantity	1600
Height	1800 mm
Quantity in layer	2
Number of layers	8
Bulk quantity	16
Weight	131,2 kg

## MORE EFFICIENCY FOR THE LED WORLD



LED line PRIME Code: 241314 EAN: 5901583241314

# LED line downlight aluminium round gold/white OLTIKA

**Example application**