

LED line LITE

Code: 203334

EAN: 5905378203334

**LUMINO Floodlight 4000K 150W
15000lm 120° IP65 LITE**



LITE LED LUMINO 150W LED line is an advanced solution with minimalistic design from aluminium casting and tempered glass, guaranteeing high durability. It emits a light stream of 15000 lm at a colour temperature of 4000 K, which provides performance of 100 lm/W. IP65 protection makes it resistant to dust and water, and class IK05 provides resistance to mechanical damage.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	F
Warranty	3
Power	• 150 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	70
IP protection rating	IP65
IK protection rating	05
IEC protection class	I
Luminous efficacy	100
Luminous flux	15000
The lumen maintenance factor	96
Lifetime L70B50	25 000 h
Survival factor	0.9

Parameter	Value
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
Beam angle	110
LED type	SMD LED
LED quantity	168
Power Factor	0,9
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Length	265
Width	327
Height	33
Weight	1530
Material (housing)	Die cast aluminium
Material (cover)	Tempered glass


LED line LITE

Code: 203334


EAN: 5905378203334

**LUMINO Floodlight 4000K 150W
15000lm 120° IP65 LITE**

Technical drawing






Light distribution



Additional product photos



Logistics data



Single packaging

Quantity	1
Width	265 mm
Height	33 mm
Length	327 mm
Weight	1,38 kg

Bulk packaging

Quantity	4
Width	275 mm
Height	175 mm
Length	355 mm
Volume	0,017 m3
Weight	5,87 kg

Europallet

Height	1950 mm
Quantity in layer	48
Number of layers	7
Bulk quantity	336
Weight	493,08 kg

LED line LITE

Code: 203334

EAN: 5905378203334

**LUMINO Floodlight 4000K 150W
15000lm 120° IP65 LITE**

Example application