

LED line PRIME


Code: 205819-DALI

EAN: 5905378220058

**Backlit Panel 4000K 34W 4760lm IP20
60x60cm white PRIME DALI**



Backlit panel 34W 4000K 4760lm 60x60 PRIME is a modern light source that provides excellent light performance at 140 lm/W. Thanks to the colour of the light 4000 K and Ra colour reproduction factor at level 80, it achieves a natural lighting effect. Offering a light stream of as many as 4,760 lumens, it fits perfectly into a variety of interiors.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	C
Warranty	5
Power	• 34 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IK protection rating	02
IEC protection class	II
Luminous efficacy	140
Luminous flux	4760
The lumen maintenance factor	96
Lifetime L70B50	50 000 h
Survival factor	0.9
Dimmable function	Dali
Colour consistency in McAdam ellipses	≤6

Parameter	Value
Frequency of the supply voltage	50/60Hz
Beam angle	90
LED type	SMD LED 2835
LED quantity	128
Power Factor	0,9
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Length	60 cm
Width	60 cm
Height	30
Colour	White
Material (housing)	Aluminium
Material (cover)	Polystyrene
DALI	• YES

LED line PRIME

Code: 205819-DALI

EAN: 5905378220058




**Backlit Panel 4000K 34W 4760lm IP20
60x60cm white PRIME DALI**

Technical drawing

Light distribution

Additional product photos

Logistics data



Single packaging

Quantity	1
Width	30 mm
Height	640 mm
Length	600 mm
Weight	1,41 kg

Bulk packaging

Quantity	5
Width	170 mm
Height	655 mm
Length	615 mm
Volume	0,075 m3
Weight	9,6 kg
Comments	

Europallet

Height	1340 mm
Quantity in layer	30
Number of layers	2
Bulk quantity	60
Weight	115,2 kg

LED line PRIME

Code: 205819-DALI

EAN: 5905378220058

**Backlit Panel 4000K 34W 4760lm IP20
60x60cm white PRIME DALI**

Example application