

LED line PRIME

Code: 201729

EAN: 5905378201729

LED bulb E14 2700K 7W 1000lm 230V
220° G45 Ceramic PRIME



LED bulb E14 7W 2700K 1000lm from LED line PRIME is a high quality light source with an elegant G45 shape. It has a luminous efficiency of 142 lm/W and a total luminous flux of 1000 lumens. Thanks to the warm white color (2700 K) creates a cozy atmosphere. Its durability is estimated at 30,000 working hours and the number of incorporation cycles is as high as 50,000. Ceramic case and glass lens provide reliability and aesthetics.

5
WARRANTY

IP
20

170-250V
AC

100-277V
AC

ON/OFF
50.000

CE

Technical data

Parameter	Value
Energy efficiency class 2019/2015	D
Warranty	5
Power	• 7 W
Voltage	• 170-250 V AC
Correlated colour temperature	• 2700 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
Luminous efficacy	142
Luminous flux	1000 lm
The lumen maintenance factor	96
Lifetime L70B50	30 000 h
Survival factor	0.9
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz

Parameter	Value
Lamp's type	G45
Beam angle	220 °
LED type	SMD2835
Power Factor	0,5
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Height	84
Fixture's diameter	45 mm
Colour	White
Material	Ceramic
Material (housing)	Ceramics
Material (cover)	glass


LED line PRIME

Code: 201729

EAN: 5905378201729

LED bulb E14 2700K 7W 1000lm 230V
220° G45 Ceramic PRIME

Technical drawing




Light distribution

Additional product photos




Logistics data




Single packaging

Quantity	1
Width	47 mm
Height	125 mm
Length	47 mm
Weight	0,06 kg



Bulk packaging

Quantity	100
Width	270 mm
Height	230 mm
Length	530 mm
Volume	0,032 m3
Weight	7 kg



Europallet

Height	1840 mm
Quantity in layer	400
Number of layers	8
Bulk quantity	3200
Weight	224 kg

LED line PRIME

Code: 201729

EAN: 5905378201729

**LED bulb E14 2700K 7W 1000lm 230V
220° G45 Ceramic PRIME**

Example application