

LED line LITE

Code: 210110

EAN: 5905378210110

**DOWNLIGHT EASY FLEX 3CCT(3K/4K/5K)
12/15/18W 1440lm square IP20 black
LITE**



Downlight EASY FLEX 18-21-24W CCT is a modern LED line LITE lighting luminaire, characterized by a luminous flux performance of 2110 lumens. It allows to choose colour temperature in the range 3000 K, 4000 K and 5000 K, which provides flexibility in space arrangement. IP20 seal class guarantees protection against solid bodies larger than 12 mm and the IK05 protection level provides impact resistance.



Technical data

| Parameter | Value |
|---------------------------------------|--|
| Energy efficiency class 2019/2015 | E |
| Warranty | 3 |
| Power | <ul style="list-style-type: none"> • 12 W • 15 W • 18 W |
| Voltage | <ul style="list-style-type: none"> • 220-240 V AC |
| Correlated colour temperature | <ul style="list-style-type: none"> • 3000 K • 4000 K • 5000 K |
| Colour of the light | CCT |
| Colour rendering index Ra | 80 |
| IP protection rating | IP20 |
| IK protection rating | 05 |
| IEC protection class | II |
| Luminous efficacy | 90 |
| Luminous flux | 1440 |
| The lumen maintenance factor | 96 |
| Lifetime L70B50 | 30 000 h |
| Colour consistency in McAdam ellipses | ≤6 |

| Parameter | Value |
|--|--|
| Frequency of the supply voltage | 50/60Hz |
| Beam angle | 120 |
| LED type | SMD2835 |
| LED quantity | 168 |
| Power Factor | ≥0,9 |
| Number of on/off cycles | 15000 |
| Lamp's warm-up time to 60% | 1 |
| Ambient temperature suitable for operation | -20÷40 |
| Installation method | 3in1 surface mounted, flush mounted, suspended |
| Mounting hole diameter | 65-175 |
| Length | 220 mm |
| Width | 220 mm |
| Height | 17 mm |
| Weight | 0,47 kg |
| Colour | White |


LED line LITE

Code: 210110


EAN: 5905378210110

**DOWNLIGHT EASY FLEX 3CCT(3K/4K/5K)
12/15/18W 1440lm square IP20 black
LITE**

Technical drawing




Light distribution



Additional product photos



Logistics data



Single packaging

| | |
|--------|---------|
| Width | 225 mm |
| Height | 58 mm |
| Length | 225 mm |
| Weight | 0,57 kg |

Bulk packaging

| | |
|----------|----------|
| Quantity | 20 |
| Width | 280 mm |
| Height | 335 mm |
| Length | 570 mm |
| Weight | 11,40 kg |

Europallet

| | |
|---------------|--------|
| Quantity | 360 |
| Height | 1,8 m |
| Bulk quantity | 18 |
| Weight | 240 kg |

LED line LITE

Code: 210110

EAN: 5905378210110

**DOWNLIGHT EASY FLEX 3CCT(3K/4K/5K)
12/15/18W 1440lm square IP20 black
LITE**

Example application