

LED line PRIME

Code: 207806

EAN: 5905378207806

Linear luminaire EXECULINE 30W
4000K 3750lm 120 cm IP20 96° white
PRIME



EXECULINE 30W 4000K 3900lm IP20 white 96° PRIME is an elegant and modern lighting element, characterized by a power of 30 W and a light stream of 3900 lm. The light colour temperature is 4000 K, which provides pleasant, neutral lighting. Made of durable aluminum and light scattering material, it guarantees even illumination at 96° angle. The life of this luminaire is estimated at 50,000 hours.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	D
Warranty	5
Power	• 30 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
IP protection rating	IP20
Luminous efficacy	130
Standby power	0
Colour consistency in McAdam ellipses	≤3
Luminous flux	3900
Survival factor	0.9
Lifetime L70B50	50 000 h

Parameter	Value
Mounting type	mixed
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80
The lumen maintenance factor	96
Beam angle	96
Power Factor	0,9
Ambient temperature suitable for operation	-15÷45
For indoor use	Inside
IEC protection class	I
Lamp's warm-up time to 60%	1 s
Length	1200
Width	35
Height	60

LED line PRIME


Code: 207806

EAN: 5905378207806

Linear luminaire EXECULINE 30W
4000K 3750lm 120 cm IP20 96° white
PRIME

Technical drawing




Light distribution



Additional product photos



Logistics data



Single packaging

Quantity	1
Width	1250 mm
Height	82 mm
Length	41 mm
Weight	1,1 kg

Bulk packaging

Quantity	10
Width	1260 mm
Height	180 mm
Length	220 mm
Volume	0,049 m3
Weight	11,35 kg
Comments	

Europallet

Height	1800 mm
Quantity in layer	200
Number of layers	10
Bulk quantity	2000
Weight	2270 kg

LED line PRIME

Code: 207806

EAN: 5905378207806

**Linear luminaire EXECULINE 30W
4000K 3750lm 120 cm IP20 96° white
PRIME**

Example application