

LED line LITE


Code: 203525

EAN: 5905378203525

**Floodlight PHOTON 4000K 30W 3000lm
120° IP65 LITE**



LITE PHOTON LED line indicator with 30W power is an advanced industrial lighting that combines high quality performance and energy efficiency. It is characterized by an impressive light stream of 3,000 lumens and a light colour of 4000 K. Its robust design with cast aluminium and tempered glass provides resistance to atmospheric conditions, and IP65 seal class guarantees effective protection against moisture and dust.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	E
Warranty	3
Power	• 30 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP65
IK protection rating	05
IEC protection class	I
Luminous efficacy	100
Luminous flux	3000
The lumen maintenance factor	96
Lifetime L70B50	30 000 h
Survival factor	0.9
Colour consistency in McAdam ellipses	≤6
ULOR	0 %

Parameter	Value
Rated power	220-240V AC
Mounting type	surface
Frequency of the supply voltage	50/60Hz
Beam angle	120
LED type	SMD2835
LED quantity	45
Power Factor	0,9
Number of on/off cycles	18000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷40
Length	149 mm
Width	136 mm
Height	34 mm
Weight	0,335 kg
Colour	Black
Material (housing)	Die cast aluminium
Material (cover)	Tempered glass


LED line LITE

Code: 203525


EAN: 5905378203525

**Floodlight PHOTON 4000K 30W 3000lm
120° IP65 LITE**

Technical drawing






Light distribution



Additional product photos



Logistics data



Single packaging

Quantity	1
Width	139 mm
Height	173 mm
Length	31 mm
Weight	0,39 kg

Bulk packaging

Quantity	20
Width	318 mm
Height	225 mm
Length	329 mm
Volume	0,023 m3
Weight	8,15 kg

Europallet

Quantity	1000
Height	1,8 m
Quantity in layer	
Number of layers	
Bulk quantity	50
Weight	440 kg

LED line LITE

Code: 203525

EAN: 5905378203525

**Floodlight PHOTON 4000K 30W 3000lm
120° IP65 LITE**

Example application