

LED line LITE

Code: 205604-AW3HAT

EAN: 5905378216709

Panel Backlit 2in1 40W 4000K 4000LM
62x62 black emergency module 3h
autotest LITE



Backlit panel 2in1 40W from LED line LITE is a modern light source of 4000K and light stream of 4000 lm. The technology used ensures uniform light distribution at 120°. The built-in emergency module guarantees the continuity of operation for 3 hours, and the autotest function allows automatic checking of battery status. The black metal housing and polystyrene cloth give an elegant look.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	E
Warranty	2
Power	• 40 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IK protection rating	02
IEC protection class	I
Luminous efficacy	100
Luminous flux	4000
The lumen maintenance factor	96
Lifetime L70B50	30 000 h

Parameter	Value
Survival factor	0.9
Dimmable function	PWM
Colour consistency in McAdam ellipses	≤6
Emergency module test	autotest
Operating time in emergency mode	3 h
Frequency of the supply voltage	50/60Hz
Beam angle	120
Power Factor	0,9
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Height	38
Material (housing)	Metal
Material (cover)	Polystyrene

LED line LITE

Code: 205604-AW3HAT

EAN: 5905378216709

Panel Backlit 2in1 40W 4000K 4000LM
62x62 black emergency module 3h
autotest LITE


Technical drawing

Light distribution


Additional product photos




Logistics data



Single packaging



Bulk packaging



Europallet

Quantity

LED line LITE

Code: 205604-AW3HAT

EAN: 5905378216709

**Panel Backlit 2in1 40W 4000K 4000LM
62x62 black emergency module 3h
autotest LITE**

Example application