

LED line PRIME

Code: 201118

EAN: 5905378201118

LED line PRIME Ceiling lamp ACTON
18W 2000lm 4000K IP54 round



The PRIME ACTON 18 W LED line and 2000 lm light stream is ideal for demanding users. Its durable design made of polycarbonate provides impact resistance (IK08) and waterproofness (IP54), making it suitable for use under different conditions. Colour temperature 4000 K generates neutral light and light efficiency at 110 lm/W guarantees low energy consumption.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	F
Warranty	5
Power	• 18 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP54
IK protection rating	08
IEC protection class	II
Luminous efficacy	110
Luminous flux	2000
The lumen maintenance factor	96
Lifetime L70B50	30 000 h
Survival factor	0.9

Parameter	Value
Dimmable function	PWM
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
Fixture's diameter	220
Beam angle	120
LED type	SMD2835
Power Factor	0,9
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-25÷40
Height	51
Weight	500
Colour	White
Material (housing)	Polycarbonate
Material (cover)	Polycarbonate


LED line PRIME

Code: 201118


EAN: 5905378201118

LED line PRIME Ceiling lamp ACTON
18W 2000lm 4000K IP54 round

Technical drawing




Light distribution



Additional product photos




Logistics data




Single packaging

Width	220 mm
Height	220 mm
Length	60 mm
Weight	0,6 kg



Bulk packaging

Quantity	20
Width	470 mm
Height	250 mm
Length	615 mm
Volume	0,072 m3
Weight	12,35 kg



Europallet

Quantity	280
Height	1,90 m
Quantity in layer	40
Number of layers	7
Bulk quantity	14
Weight	198 kg

LED line PRIME

Code: 201118

EAN: 5905378201118

**LED line PRIME Ceiling lamp ACTON
18W 2000lm 4000K IP54 round**

Example application