

LED line PRIME


Code: 475923

EAN: 5907777475923

LED line PRIME FUSION linear lamp
40W 4000K 5200lm 0-10V P18° black



The FUSION 40W LED line PRIME is characterized by light efficiency of 130 lm/W and a total light stream of 5200 lumens. With colour temperature 4000K provides bright, neutral light. Made of high quality aluminum, it effectively drains heat, which increases the durability to 50,000 hours. It offers the possibility to adjust the lighting angle using lenses and supports dimming of the 0-10V standard.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	C
Warranty	5
Power	• 40 W
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IK protection rating	08
IEC protection class	I
Luminous efficacy	130
Luminous flux	5200
The lumen maintenance factor	96
Lifetime L70B50	50 000 h
Survival factor	0.9

Parameter	Value
Dimmable function	0-10
Colour consistency in McAdam ellipses	≤6
Sling length	200 cm
Standby power	0
Mounting type	mixed
Frequency of the supply voltage	50/60Hz
Power Factor	0,9
Lamp's warm-up time to 60%	1 s
Ambient temperature suitable for operation	-20÷45
For indoor use	Inside
Length	1158
Width	70
Height	52

LED line PRIME

Code: 475923


EAN: 5907777475923

LED line PRIME FUSION linear lamp
40W 4000K 5200lm 0-10V P18° black

Technical drawing




Light distribution



Additional product photos




Logistics data




Single packaging

Width	1158 mm
Height	52 mm
Length	70 mm
Weight	1,82 kg



Bulk packaging

Quantity	12
Width	1260 mm
Height	260 mm
Length	260 mm
Volume	0,085 m3
Weight	22,09 kg
Comments	



Europallet

Quantity	144
Height	1260 mm
Quantity in layer	144
Number of layers	1
Bulk quantity	144
Weight	265,2 kg

LED line PRIME

Code: 475923

EAN: 5907777475923

**LED line PRIME FUSION linear lamp
40W 4000K 5200lm 0-10V P18° black**

Example application