

LED line LITE

Code: 210134

EAN: 5905378210134

**DOWNLIGHT EASY FLEX 3CCT(3K/4K/5K)
18/21/24W 2000lm square IP20 black
LITE**



Downlight EASY FLEX 18-21-24W CCT is a modern LED line LITE lighting luminaire, characterized by a luminous flux performance of 2110 lumens. It allows to choose colour temperature in the range 3000 K, 4000 K and 5000 K, which provides flexibility in space arrangement. IP20 seal class guarantees protection against solid bodies larger than 12 mm and the IK05 protection level provides impact resistance.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	E
Warranty	3
Power	<ul style="list-style-type: none"> • 18 W • 21 W • 24 W
Voltage	<ul style="list-style-type: none"> • 220-240 V AC
Correlated colour temperature	<ul style="list-style-type: none"> • 3000 K • 4000 K • 5000 K
Colour of the light	CCT
Colour rendering index Ra	80
IP protection rating	IP20
IK protection rating	05
IEC protection class	II
Luminous efficacy	83
Luminous flux	2000
The lumen maintenance factor	96
Lifetime L70B50	30 000 h
Colour consistency in McAdam ellipses	≤6

Parameter	Value
Frequency of the supply voltage	50/60Hz
Beam angle	120
LED type	SMD2835
LED quantity	168
Power Factor	≥0,9
Number of on/off cycles	15000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷40
Installation method	3in1 surface mounted, flush mounted, suspended
Mounting hole diameter	65-240
Length	295 mm
Width	295 mm
Height	17 mm
Weight	0,74 kg
Colour	White


LED line LITE

Code: 210134


EAN: 5905378210134

**DOWNLIGHT EASY FLEX 3CCT(3K/4K/5K)
18/21/24W 2000lm square IP20 black
LITE**

Technical drawing



Light distribution



Additional product photos



Logistics data



Single packaging

Width	330 mm
Height	31 mm
Length	300 mm
Weight	0,94 kg

Bulk packaging

Quantity	10
Width	350 mm
Height	315 mm
Length	335 mm
Weight	9,4 kg

Europallet

Quantity	300
Height	1,8 m
Bulk quantity	30
Weight	310 kg

LED line LITE

Code: 210134

EAN: 5905378210134

**DOWNLIGHT EASY FLEX 3CCT(3K/4K/5K)
18/21/24W 2000lm square IP20 black
LITE**

Example application