

LED line PRIME

Code: 470720

EAN: 5907777470720

LED line PRIME SMD 5W 2700K 400lm
220-260V 50mm DIM



LED line bulb PRIME SMD 5W 2700K is a unique light source with a stream of 400 lumens and a warm colour of 2700 K. Made of ceramics and glass, it provides high quality and aesthetic design. With a PF power factor of 0.5 and a light output of 80 lm/W, it offers an energy-efficient solution.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	G
Energy class	A+
Warranty	3
Power	• 5 W
Voltage	• 220-260 V AC
Correlated colour temperature	• 2700 K
Colour of the light	White
Colour rendering index Ra	80
IEC protection class	II
Luminous efficacy	80
Luminous flux	400
The lumen maintenance factor	96
Lifetime L70B50	30 000 h
Survival factor	0.9
Dimmable function	Triac

Parameter	Value
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
Fixture's diameter	50 mm
Beam angle	110
LED type	SMD2835
Compatible dimmer type	TRIAC
Power Factor	0,5
Number of on/off cycles	50000
Ambient temperature suitable for operation	-5÷40
For indoor use	Inside
Height	22
Colour	White
Material (housing)	Ceramics
Material (cover)	glass

LED line PRIME

Code: 470720

EAN: 5907777470720


LED line PRIME SMD 5W 2700K 400lm

220-260V 50mm DIM


Technical drawing




Light distribution



Additional product photos




Logistics data




Single packaging

Quantity	10
Width	47 mm
Height	125 mm
Length	47 mm
Weight	0,08 kg



Bulk packaging

Quantity	100
Width	290 mm
Height	170 mm
Length	595 mm
Volume	0,029 m3
Weight	7 kg
Comments	



Europallet

Quantity	4500
Height	1870 mm
Quantity in layer	400
Number of layers	11
Bulk quantity	4400
Weight	308 kg

LED line PRIME

Code: 470720

EAN: 5907777470720

**LED line PRIME SMD 5W 2700K 400lm
220-260V 50mm DIM**

Example application