

LED line PRIME


Code: 477217

EAN: 5907777477217

LED strip 300/5m SMD 12V 6500K 4,8W
IP20 8mm 50m 480lm/m PRIME



LED strip 300 SMD 12V 6500K 4.8W 50m from PRIME LED line is an advanced lighting source that offers excellent light performance of 83 lm/W. Thanks to the use of SMD 3528 diodes and high quality laminate, it ensures long-term use of up to 30,000 hours. By offering light colour in the range of 6500K, it effectively maps colors. The tape is also characterized by a kind of MWM dimming function and IP20 leak class.



Technical data

Parameter	Value	Parameter	Value
Energy efficiency class 2019/2015	G	Wire length	200 mm
Warranty	5	Luminous flux (lm)	400
Power	• 4.8 W / m	Current (Im)	0,4
Voltage	• 12 V DC	Beam angle	120
Correlated colour temperature	• 6500 K	LED type	SMD 3528
Colour of the light	White	LED quantity	300
Colour rendering index Ra	80	Compatible dimmer type	PWM
IP protection rating	IP20	Laminate (colour)	White
IEC protection class	III	Laminate (thickness)	2
Cutting section	5 cm	LED quantity (lm)	60
Luminous efficacy	83	Type of adhesive tape	3M 300 LSE
The lumen maintenance factor	96	Ambient temperature suitable for operation	-25÷45
Lifetime L70B50	30 000 h	For indoor use	Inside
Survival factor	0.9	Length	50000
Dimmable function	PWM	Height	2,5
Colour consistency in McAdam ellipses	≤3		


LED line PRIME

Code: 477217


EAN: 5907777477217

LED strip 300/5m SMD 12V 6500K 4,8W
IP20 8mm 50m 480lm/m PRIME

Technical drawing




Light distribution




Additional product photos

Logistics data




Single packaging

Width	153 mm
Height	15 mm
Length	153 mm
Weight	0,81 kg



Bulk packaging

Quantity	20
Width	520 mm
Height	350 mm
Length	520 mm
Volume	0,094 m3
Weight	15,18 kg
Comments	



Europallet

Quantity	10000 m
Height	1750 mm
Quantity in layer	40 szt.
Number of layers	5
Bulk quantity	200 szt.
Weight	202,4

LED line PRIME

Code: 477217

EAN: 5907777477217

**LED strip 300/5m SMD 12V 6500K 4,8W
IP20 8mm 50m 480lm/m PRIME**

Example application