

LED line PRIME

Code: 202696

EAN: 5905378202696

FLOODLIGHT 4000K 400W 56000lm T3 IP66 PRIME



The PRIME Floodlight 400W LED line reflector is a versatile lighting setting offering an impressive light stream of 56,000 lumens. Thanks to the colour of the light 4000 K and the colour reproduction coefficient Ra at level 70, it provides natural color rendering. Energy efficiency class D and power factor PF 0.9 confirm the efficiency of the device.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	D
Warranty	5/7*
Power	• 400 W
Voltage	• 100-277 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	70
IP protection rating	IP66
IK protection rating	08
IEC protection class	I
Luminous efficacy	140
Luminous flux	56000
The lumen maintenance factor	96
Lifetime L70B50	50 000 h
L80B* – difference B10–B50 ≈ 1% (according to LightingEurope) – negligible	35000 h

Parameter	Value
Survival factor	0.9
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
Beam angle	105°x155
LED type	SMD2835
LED quantity	720
Power Factor	>=0,9
Number of on/off cycles	50000
Ambient temperature suitable for operation	-40÷45
Length	450 mm
Width	490 mm
Height	52 mm
Material (housing)	Aluminium
Material (cover)	Tempered glass


LED line PRIME

Code: 202696


EAN: 5905378202696

**FLOODLIGHT 4000K 400W 56000lm T3
IP66 PRIME**


Technical drawing






Light distribution



Additional product photos



Logistics data



Single packaging

Width	500 mm
Height	58 mm
Length	480 mm
Weight	7,65 kg

Bulk packaging

Quantity	1
Width	550 mm
Height	82 mm
Length	560 mm
Volume	0,025 m3
Weight	7,65 kg
Comments	

Europallet

Quantity	36
Height	1886 mm
Quantity in layer	2
Number of layers	23
Bulk quantity	46
Weight	25 kg

LED line PRIME

Code: 202696

EAN: 5905378202696

**FLOODLIGHT 4000K 400W 56000lm T3
IP66 PRIME**

Example application