

LED line PRIME


Code: 201095

EAN: 5905378201095

LED line PRIME Ceiling lamp ACTON
18W 1900lm 3000K IP54 round



ACTON Plafon from LED line PRIME is a modern light source with a power of 18 W, generating an impressive light stream of 1900 lm. Its colour temperature is a pleasant warm white light 3000 K, ideal for creating an atmosphere in different spaces. The housing is characterized by a durable polycarbonate structure, providing impact protection (IK08) and high IP54 tightness, which allows installation both inside and outside buildings.



Technical data

Parameter	Value	Parameter	Value
Energy efficiency class 2019/2015	F	Dimmable function	PWM
Warranty	5	Colour consistency in McAdam ellipses	≤6
Power	• 18 W	Frequency of the supply voltage	50/60Hz
Voltage	• 220-240 V AC	Fixture's diameter	220
Correlated colour temperature	• 3000 K	Beam angle	120
Colour of the light	White	LED type	SMD2835
Colour rendering index Ra	80	Power Factor	0,9
IP protection rating	IP54	Lamp's warm-up time to 60%	1
IK protection rating	08	Ambient temperature suitable for operation	-25÷40
IEC protection class	II	Height	51
Luminous efficacy	105	Weight	500
Luminous flux	1900	Colour	White
The lumen maintenance factor	96	Material (housing)	Polycarbonate
Lifetime L70B50	30 000 h	Material (cover)	Polycarbonate
Survival factor	0.9		


LED line PRIME

Code: 201095


EAN: 5905378201095

LED line PRIME Ceiling lamp ACTON
18W 1900lm 3000K IP54 round

Technical drawing




Light distribution



Additional product photos




Logistics data




Single packaging

Width	220 mm
Height	220 mm
Length	60 mm
Weight	0,6 kg



Bulk packaging

Quantity	20
Width	470 mm
Height	250 mm
Length	615 mm
Volume	0,072 m3
Weight	12,35 kg



Europallet

Quantity	400
Height	1750 mm
Quantity in layer	40
Number of layers	7
Bulk quantity	280
Weight	172,9 kg

LED line PRIME

Code: 201095

EAN: 5905378201095

**LED line PRIME Ceiling lamp ACTON
18W 1900lm 3000K IP54 round**

Example application