

LED line PRIME


Code: 210493

EAN: 5905378210493

Track light LUMICANTO 6-20W CCT 36/60° black PRIME



Track light LUMICANTO 6-20W CCT 36/60° in black, is a modern LED line PRIME lighting setting. It uses innovative COB-Bridgelux diodes, characterized by high light performance of up to 110 lm/W and variable colour temperature: 3000 K, 4000 K and 6000 K. The luminaire provides excellent colour reproduction ( $Ra \geq 90$ ) and a low flickering factor. With IP20 and IK06 certifications, it offers reliability in different conditions, and its durability is as high as 50,000 hours.



Technical data

| Parameter                             | Value                           | Parameter                                  | Value         |
|---------------------------------------|---------------------------------|--|---------------|
| Energy efficiency class 2019/2015     | E                               | Mounting type                              | 3 phase rail  |
| Warranty                              | 5                               | Frequency of the supply voltage            | 50/60Hz       |
| Power                                 | • 6-20 W                        | Fixture's diameter                         | 100 mm        |
| Voltage                               | • 220-240 V AC                  | Beam angle                                 | 60/36         |
| Correlated colour temperature         | • 3000 K<br>• 4000K<br>• 6000 K | LED type                                   | COB-Bridgelux |
| Colour of the light                   | White                           | LED quantity                               | 1             |
| Colour rendering index Ra             | 90                              | Power Factor                               | >0,7          |
| IP protection rating                  | IP20                            | Number of on/off cycles                    | 25000         |
| IK protection rating                  | 06                              | Ambient temperature suitable for operation | 5÷40          |
| IEC protection class                  | II                              | For indoor use                             | Inside        |
| Luminous efficacy                     | do 110                          | Width                                      | 152           |
| Luminous flux                         | 620-2000                        | Height                                     | 165           |
| The lumen maintenance factor          | 96                              | Colour                                     | Black         |
| Lifetime L70B50                       | 50 000 h                        | Material (housing)                         | Aluminium     |
| Survival factor                       | 0,9                             | Material (cover)                           | clear glass   |
| Colour consistency in McAdam ellipses | ≤3                              |  |               |

LED line PRIME

Code: 210493


EAN: 5905378210493

Track light LUMICANTO 6-20W CCT  
36/60° black PRIME




Technical drawing

Light distribution

Additional product photos



Logistics data



Single packaging

|        |         |
|--------|---------|
| Width  | 108 mm  |
| Height | 175 mm  |
| Length | 186 mm  |
| Weight | 0,67 kg |

Bulk packaging

|          |          |
|----------|----------|
| Quantity | 20       |
| Width    | 385 mm   |
| Height   | 365 mm   |
| Length   | 565 mm   |
| Volume   | 0,079 m3 |
| Weight   | 16,8 kg  |

Europallet

|                   |         |
|-------------------|---------|
| Height            | 1825 mm |
| Quantity in layer | 80      |
| Number of layers  | 5       |
| Bulk quantity     | 400     |
| Weight            | 368 kg  |

---

LED line PRIME

Code: 210493

EAN: 5905378210493

**Track light LUMICANTO 6-20W CCT  
36/60° black PRIME**

---

**Example application**