

LED line LITE


Code: 203297

EAN: 5905378203297

**LUMINO Floodlight 4000K 20W 2000lm
120° IP65 LITE**



The 20W LUMino LED light bulb emits a white light with a colour temperature of 4000 K, generating an impressive light stream of 2,000 lm. The output is 100 lm/W and the high power factor PF is 0.9. The IP65 class provides excellent protection against dust and water, making it resistant to adverse weather conditions.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	F
Warranty	3
Power	• 20 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	70
IP protection rating	IP65
IK protection rating	05
IEC protection class	I
Luminous efficacy	100
Luminous flux	2000
The lumen maintenance factor	96
Lifetime L70B50	25 000 h
Survival factor	0.9

Parameter	Value
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
Beam angle	110
LED type	SMD LED
LED quantity	28
Power Factor	0,9
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Length	114
Width	126,5
Height	29
Weight	240
Material (housing)	Die cast aluminium
Material (cover)	Tempered glass


LED line LITE

Code: 203297


EAN: 5905378203297

**LUMINO Floodlight 4000K 20W 2000lm
120° IP65 LITE**

Technical drawing






Light distribution



Additional product photos



Logistics data



Single packaging

Quantity	1
Width	114 mm
Height	29 mm
Length	126,5 mm
Weight	0,22 kg

Bulk packaging

Quantity	20
Width	250 mm
Height	190 mm
Length	285 mm
Volume	0,013 m3
Weight	4,75 kg

Europallet

Height	1750 mm
Quantity in layer	320
Number of layers	7
Bulk quantity	2240
Weight	532 kg

LED line LITE

Code: 203297

EAN: 5905378203297

**LUMINO Floodlight 4000K 20W 2000lm
120° IP65 LITE**

Example application