

LED line LITE

Code: 201040

EAN: 5905378201040

DOWNLIGHT MOLLY 4000K 5W 500lm square IP20 White LITE



LED line LITE Downlight MOLLY 5W emits a total luminous flux of 500 lm at a colour temperature of 4000 K. It is characterized by a minimalist design, which makes it perfectly fit into a variety of interior arrangements. High light efficiency at 100 lm/W and Ra>80 colour rendering rate provide natural color reproduction. The housing has IP20 leak class and can be mounted both under the surface and surface.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	D
Warranty	3
Power	• 5 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IEC protection class	II
Luminous efficacy	100
Luminous flux	500
The lumen maintenance factor	96
Lifetime L70B50	30 000 h
Survival factor	0.9
Colour consistency in McAdam ellipses	≤6

Parameter	Value
Frequency of the supply voltage	50/60Hz
LED type	SMD LED 2835
LED quantity	30
Power Factor	≥0,5
Number of on/off cycles	20000
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Mounting hole diameter	75-90
Length	95
Width	95
Height	26
Weight	0,063 kg
Colour	White
Material (housing)	Polycarbonate


LED line LITE

Code: 201040


EAN: 5905378201040

DOWNLIGHT MOLLY 4000K 5W 500lm square IP20 White LITE

Technical drawing





Light distribution



Additional product photos



Logistics data



Single packaging

Quantity	1
Width	95 mm
Height	26 mm
Length	95 mm
Weight	0,09 kg

Bulk packaging

Quantity	100
Width	390 mm
Height	220 mm
Length	525 mm
Volume	0,045 m3
Weight	12,1 kg

Europallet

Quantity	4800
Height	1,80 m
Quantity in layer	600
Number of layers	8
Bulk quantity	48
Weight	611 kg

LED line LITE

Code: 201040

EAN: 5905378201040

**DOWNLIGHT MOLLY 4000K 5W 500lm
square IP20 White LITE**

Example application

