

LED line PRIME

Code: 201125

EAN: 5905378201125

LED line PRIME Ceiling lamp ACTON
18W 2000lm 4000K IP54 round with
motion sensor



The ACTON LED line PRIME is a harmonious combination of modernity and functionality. With 18 W power, it achieves an impressive light stream of 2000 lm, which provides performance of 110 lm/W. Its white color and color temperature 4000 K create pleasant lighting, ideal for different spaces. The use of a polycarbonate housing guarantees high impact resistance (IK08) and IP54 tightness.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	F
Warranty	5
Power	• 18 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP54
IK protection rating	08
IEC protection class	II
Luminous efficacy	110
Luminous flux	2000
The lumen maintenance factor	96
Lifetime L70B50	30 000 h
Survival factor	0.9
Dimmable function	PWM

Parameter	Value
Colour consistency in McAdam ellipses	≤6
Hold time	90 s
Frequency of the supply voltage	50/60Hz
Fixture's diameter	220
Beam angle	120
Motion detection range and angle	360° 8m
LED type	SMD2835
Power Factor	0,9
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-25÷40
Height	51
Weight	500
Colour	White
Material (housing)	Polycarbonate
Material (cover)	Polycarbonate


LED line PRIME

Code: 201125


EAN: 5905378201125

LED line PRIME Ceiling lamp ACTON
18W 2000lm 4000K IP54 round with
motion sensor

Technical drawing






Light distribution



Additional product photos



Logistics data



Single packaging

Width	220 mm
Height	220 mm
Length	60 mm
Weight	0,6 kg

Bulk packaging

Quantity	20
Width	470 mm
Height	250 mm
Length	615 mm
Volume	0,072 m3
Weight	12,35 kg

Europallet

Quantity	280
Height	1,90 m
Quantity in layer	40
Number of layers	7
Bulk quantity	14
Weight	198 kg

LED line PRIME

Code: 201125

EAN: 5905378201125

**LED line PRIME Ceiling lamp ACTON
18W 2000lm 4000K IP54 round with
motion sensor**

Example application