

LED line LITE Code: 203372 EAN: 5905378203372

# LED line LITE Floodlight LUMINO 30W 4000K 3000lm with motion sensor





LUMINO 30W 4000K LED is an innovative lighting solution with a power of 30 watts and a light stream of 3000 lm. With SMD LED technology, it achieves performance of 100 lm/W. The housing is made of durable cast aluminium and tempered glass, which provides high resistance to atmospheric conditions.















#### **Technical data**

Parameter	Value
Energy efficiency class 2019/2015	F
Warranty	3
Power	• 30 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	70
IP protection rating	IP44
IK protection rating	05
IEC protection class	1
Luminous efficacy	100
Luminous flux	3000
The lumen maintenance factor	96
Lifetime L70B50	25 000 h
Survival factor	0.9
Colour consistency in McAdam ellipses	<b>≤</b> 6


Parameter	Value
Hold time	10s - 10min
Frequency of the supply voltage	50/60Hz
Beam angle	110
Sensor type	PIR
LED type	SMD LED
LED quantity	28
Power Factor	0,9
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Length	164
Width	167
Height	79
Weight	380
Material (housing)	Die cast aluminium
Material (cover)	Tempered glass



LED line LITE Code: 203372 EAN: 5905378203372

# LED line LITE Floodlight LUMINO 30W 4000K 3000lm with motion sensor

### **Technical drawing**



### **Light distribution**



STN23\*QuerV


#### Additional product photos







### Logistics data

Single packaging









Bulk packag

Quantity	1
Width	164 mm
Height	79 mm
Length	167 mm
Weight	0,36 kg

Quantity	20
Width	360 mm
Height	340 mm
Length	385 mm
Volume	0,047 m3
Weight	7,55 kg

#### Europallet

Height	1925 mm
Quantity in layer	120
Number of layers	5
Bulk quantity	600
Weight	226,5 kg
•	

## MORE EFFICIENCY FOR THE LED WORLD



LED line LITE Code: 203372 EAN: 5905378203372

# LED line LITE Floodlight LUMINO 30W 4000K 3000lm with motion sensor

**Example application**