

LED line LITE

Code: 470652

EAN: 5907777470652

LED line® Panel Easy Fix AURA smart
18W 2800-6500K round



LED line Panel Easy Fix AURA smart 18W round-shaped is an innovative solution that combines aesthetics with functionality. Thanks to the adjustable colour temperature from 2800 K to 6500 K and the light stream from 1200 to 1400 lumens, it provides excellent lighting. The product is made of polyamide and polystyrene, which guarantees durability and reliability. IP20 leak class indicates its purpose for interiors.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	E
Energy class	A++
Warranty	3
Power	• 18 W
Voltage	• 220-260 V AC
Correlated colour temperature	• 2800-6500 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IEC protection class	II
Luminous efficacy	61-78
Luminous flux	1200-1400
The lumen maintenance factor	96
Lifetime L70B50	30 000 h
Survival factor	0.9
Dimmable function	Tuya

Parameter	Value
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
Fixture's diameter	217 mm
Beam angle	120
LGP	PMMA
LED type	2835
LED quantity	164
Power Factor	0,5
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-5÷40
For indoor use	Inside
Mounting hole diameter	60-185
Height	15
Material (housing)	Polyamide
Material (cover)	Polystyrene

LED line LITE


Code: 470652

EAN: 5907777470652

LED line® Panel Easy Fix AURA smart
18W 2800-6500K round

Technical drawing


Light distribution



Additional product photos




Logistics data




Single packaging

Quantity	1
Width	220 mm
Height	44 mm
Length	220 mm
Weight	0,69 kg



Bulk packaging

Quantity	20
Width	250 mm
Height	480 mm
Length	480 mm
Volume	0,057 m3
Weight	17,97 kg
Comments	



Europallet

Quantity	420
Height	1920 mm
Quantity in layer	120
Number of layers	4
Bulk quantity	480
Weight	324 kg

LED line LITE

Code: 470652

EAN: 5907777470652

**LED line® Panel Easy Fix AURA smart
18W 2800-6500K round**

Example application