

LED line PRIME


Code: 207127

EAN: 5905378207127

**Park luminaire Nolina 30W 4000K
4500lm black PRIME**



The NOLINA 30W LED line PRIME is an advanced lighting solution, offering a power of 30 W and a light stream of 4500 lm. It is characterized by high light performance of 150 lm/W and 4,000 K light colour, which ensures excellent lighting quality. Made of durable aluminium casting and polycarbonate, it has IP66 leak class and IK08 resistance.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	C
Warranty	5
Power	• 30 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	70
IP protection rating	IP66
IK protection rating	08
IEC protection class	I
Luminous efficacy	150
Luminous flux	4500
The lumen maintenance factor	96
Lifetime L70B50	70 000 h
Survival factor	0.9
Colour consistency in McAdam ellipses	≤6

Parameter	Value
Wire length	550 mm
Frequency of the supply voltage	50/60Hz
Fixture's diameter	450
Beam angle	100
LED type	SMD LED
Power Factor	0,92
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1s
Ambient temperature suitable for operation	-40+50
Width	450
Height	577
Weight	5900
Colour	Black
Material (housing)	Die cast aluminium
Material (cover)	polycarbonate

LED line PRIME

Code: 207127


EAN: 5905378207127

**Park luminaire Nolina 30W 4000K
4500lm black PRIME**




Technical drawing

Light distribution

Additional product photos



Logistics data



Single packaging

Bulk packaging

Europallet

Quantity	1
Width	485 mm
Height	635 mm
Length	485 mm
Weight	7,76 kg

Quantity	1
Width	485 mm
Height	635 mm
Length	485 mm
Weight	5,9 kg

LED line PRIME

Code: 207127

EAN: 5905378207127

**Park luminaire Nolina 30W 4000K
4500lm black PRIME**

Example application