

LED line LITE


Code: 206748

EAN: 5905378206748

LED line LITE HighBay luminaire
STREAKBAY 50W 4000K 10000lm



LED STREAKBAY High 50W Bay and 5000 lm light stream is a modern lighting solution that is characterized by high performance, reaching 100 lm/W. Thanks to the colour temperature of 4000K and the asymmetric lens 120x60°, it provides even illumination for large spaces with minimal light scattering. Made of solid cast aluminium housing and high degree of protection IP65 guarantee resistance to difficult operating conditions.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	E
Warranty	5
Power	• 50 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IK protection rating	08
IEC protection class	I
Luminous efficacy	100
Luminous flux	5000
The lumen maintenance factor	96
Lifetime L70B50	36 000 h
Survival factor	0.9

Parameter	Value
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
Beam angle	120x60
LED type	SMD LED
LED quantity	54
Power Factor	0,95
Ambient temperature suitable for operation	-40÷40
Length	285
Width	118
Height	78
Weight	860
Material (housing)	Die cast aluminium
Material (cover)	polycarbonate


LED line LITE

Code: 206748

EAN: 5905378206748

LED line LITE HighBay luminaire
STREAKBAY 50W 4000K 10000lm

Technical drawing




Light distribution

Additional product photos




Logistics data




Single packaging

Quantity	1
Width	285 mm
Height	78 mm
Length	118 mm
Weight	0,85 kg



Bulk packaging

Quantity	10
Width	310 mm
Height	275 mm
Length	485 mm
Volume	0,041 m3
Weight	10,2 kg



Europallet

Height	1925 mm
Quantity in layer	40
Number of layers	7
Bulk quantity	280
Weight	285,6 kg

LED line LITE

Code: 206748

EAN: 5905378206748

**LED line LITE HighBay luminaire
STREAKBAY 50W 4000K 10000lm**

Example application