

LED line LITE Code: 203792 EAN: 5905378203792

### LED line LITE Road luminaire FLAMINGO 50W 4000K 5000lm grey





FLAMINGO 50W road luminaire from LED line LITE is a reliable lighting solution, providing a light stream of 5,000 lumens with a light colour of 4000 K. Made of permanent aluminium casting, the housing is characterized by resistance to adverse weather conditions, achieving the degree of protection IP65 and IK08.

















#### **Technical data**

Parameter	Value
Energy efficiency class 2019/2015	E
Warranty	3
Power	• 50 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IEC protection class	1
Luminous flux	5000
The lumen maintenance factor	96
Lifetime L70B50	25 000 h
Survival factor	0.9
Colour consistency in McAdam ellipses	<b>≤</b> 6
ULOR	0 %
Wire length	300 mm

Parameter	Value
Mounting type	mixed
Frequency of the supply voltage	50/60Hz
Beam angle	140 x 70
LED type	SMD LED
LED quantity	72
Power Factor	0,9
Lamp's warm-up time to 60%	1 s
Ambient temperature suitable for operation	-25÷50
Length	508
Width	89
Height	108
Weight	770
Colour	Grey
Material (cover)	polycarbonate




LED line LITE Code: 203792 EAN: 5905378203792

# LED line LITE Road luminaire FLAMINGO 50W 4000K 5000lm grey


#### **Technical drawing**

#### **Light distribution**

#### Luminous [cd/klm]




#### Additional product photos








### Logistics data






Quantity	1
Width	508 mm
Height	108 mm
Length	89 mm
Weight	0,9 kg



**Bulk packaging** 

Quantity	20
Width	475 mm
Height	440 mm
Length	530 mm
Volume	0,110 m3
Weight	18,35 kg



Europallet

Height	1760 mm
Quantity in layer	40
Number of layers	4
Bulk quantity	160
Weight	146,8 kg

### MORE EFFICIENCY FOR THE LED WORLD



LED line LITE Code: 203792 EAN: 5905378203792

# LED line LITE Road luminaire FLAMINGO 50W 4000K 5000lm grey

**Example application**