

LED line LITE

Code: 200821

EAN: 5905378200821

Downlight MOLLY 24W 2550lm 4000K
round LITE



LED line setting LITE Downlight MOLLY 24W with a light stream of 2550 lm and a colour temperature of 4000 K is characterized by high efficiency, achieving performance of 105 lm/W. IP20 leak class and energy class D provides durability and adequate protection against dust. The high quality of polycarbonate production guarantees long-term use.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	D
Warranty	3
Power	• 24 W
Voltage	• 170-260 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IEC protection class	II
Luminous efficacy	105
Luminous flux	2550
The lumen maintenance factor	96
Lifetime L70B50	30 000 h
Survival factor	0.9
Colour consistency in McAdam ellipses	≤6

Parameter	Value
Frequency of the supply voltage	50/60Hz
Fixture's diameter	220 mm
Beam angle	110
LED type	SMD LED 2835
LED quantity	120
Power Factor	0,5
Number of on/off cycles	20000
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Mounting hole diameter	190-210
Height	26
Weight	205
Colour	White
Material (housing)	Polycarbonate


LED line LITE

Code: 200821


EAN: 5905378200821

Downlight MOLLY 24W 2550lm 4000K
round LITE

Technical drawing






Light distribution



Additional product photos



Logistics data



Single packaging

Width	228 mm
Height	35 mm
Length	225 mm
Weight	0,21 kg

Bulk packaging

Quantity	40
Width	480 mm
Height	390 mm
Length	480 mm
Volume	0,015 m3
Weight	12,7 kg

Europallet

Quantity	640
Height	1,90 m
Quantity in layer	160
Number of layers	4
Bulk quantity	16
Weight	1041 kg

LED line LITE

Code: 200821

EAN: 5905378200821

**Downlight MOLLY 24W 2550lm 4000K
round LITE**

Example application

