

LED line LITE

Code: 477613

EAN: 5907777477613

**Hermetic luminaire TRI-PROOF 4000K
40W 4800lm IP65 120cm gray LITE**



LED line LITE TRI-PROOF 40W is an innovative solution with a length of 1250 mm and a colour temperature of 4000K. Thanks to the impact-resistant polycarbonate housing and increased IP65 protection, it provides excellent tightness and durability in difficult conditions. Light efficiency is 4800 lumens at 40W, which guarantees energy-efficient use.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	E
Warranty	3
Power	• 40 W
Voltage	• 185-265 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP65
IK protection rating	08
IEC protection class	II
Luminous efficacy	120
Luminous flux	4800
The lumen maintenance factor	96
Lifetime L70B50	35 000 h
Survival factor	0.9
Colour consistency in McAdam ellipses	≤6
ULOR	10 %
Standby power	0

Parameter	Value
Mounting type	surface
Frequency of the supply voltage	50/60Hz
CRI colour rendering index	80
Beam angle	120
LED type	2835
LED quantity	144
Lifespan	35 000 h
Power Factor	0,9
Number of on/off cycles	20000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷40
Length	1200 mm
Width	82 mm
Height	50 mm
Weight	0,53 kg
Colour	White
Material (housing)	Polycarbonate
Material (cover)	Polycarbonate


LED line LITE

Code: 477613


EAN: 5907777477613

**Hermetic luminaire TRI-PROOF 4000K
40W 4800lm IP65 120cm gray LITE**

Technical drawing



Light distribution



Additional product photos



Logistics data



Single packaging

Quantity	1
Width	1250 mm
Height	48 mm
Length	82 mm
Weight	0,6 kg

Bulk packaging

Quantity	10
Width	270 mm
Height	190 mm
Length	1260 mm
Volume	0,064 m3
Weight	9,35 kg
Comments	

Europallet

Quantity	160
Height	1,6 m
Quantity in layer	160
Number of layers	1
Bulk quantity	16
Weight	175 kg

LED line LITE

Code: 477613

EAN: 5907777477613

**Hermetic luminaire TRI-PROOF 4000K
40W 4800lm IP65 120cm gray LITE**

Example application