

LED line LITE

Code: 203921

EAN: 5905378203921

Panel Backlit 2in1 40W 4000K 4000LM  
595x595 White LITE



Backlit panel 2in1 40W 4000K 4000LM with dimensions of 595x595 mm is an innovative LED LED setting from LITE line, distinguished by its high quality performance and efficiency. Thanks to the use of SMD LEDs, it offers excellent light performance of 100 lm/W and a stable light stream of 4000 lm. The housing allows for easy installation of both surface and surface in Armstrong ceiling systems.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	E
Warranty	2
Power	<ul style="list-style-type: none"><li>40 W</li></ul>
Voltage	<ul style="list-style-type: none"><li>220-240 V AC</li></ul>
Correlated colour temperature	<ul style="list-style-type: none"><li>4000 K</li></ul>
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IK protection rating	02
IEC protection class	I
Luminous efficacy	100
Luminous flux	4000

Parameter	Value
The lumen maintenance factor	96
Lifetime L70B50	30 000 h
Survival factor	0.9
Dimmable function	PWM
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
Power Factor	0.9
Lamp's warm-up time to 60%	1 s
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Material (housing)	Metal
Material (cover)	polystyrene

LED line LITE


Code: 203921

EAN: 5905378203921

Panel Backlit 2in1 40W 4000K 4000LM  
595x595 White LITE

Technical drawing


Light distribution



Additional product photos




Logistics data




Single packaging

Width	605 mm
Height	45 mm
Length	605 mm
Weight	1,37 kg



Bulk packaging

Quantity	6
Width	300 mm
Height	625 mm
Length	625 mm
Volume	0,117 m3
Weight	8,52 kg



Europallet

Height	1860 mm
Quantity in layer	24
Number of layers	3
Bulk quantity	72
Weight	102,24 kg

---

LED line LITE

Code: 203921

EAN: 5905378203921

**Panel Backlit 2in1 40W 4000K 4000LM  
595x595 White LITE**

---

**Example application**