

LED line PRIME

Code: 244810

EAN: 5901583244810

LED line downlight aluminium round adjustable silver brushed

The PRIME LED line ceiling housing in silver brushed color is a modern and elegant solution for interiors. The 83 mm diameter and the possibility to use bulbs up to 35 W provide versatility in the field of lighting. The moving mechanism allows for precise setting of the lighting angle, which affects the efficiency of space lighting. IP20 protection class and insulation class III guarantee safety of use.



Technical data

Parameter	Value
Warranty	5
IP protection rating	IP20
IEC protection class	III
Maximum suitable lamp power	35 W
Fixture's diameter	83
Lamp's diameter	50 mm
Y-axis angle regulation	35

Parameter	Value
Type of surface suitable for installation	F
Distance from illuminated surface	0.5 m
Installation method	recessed
Mounting hole diameter	70
Height	25
Colour	silver
Material (housing)	Aluminium


LED line PRIME

Code: 244810

EAN: 5901583244810

LED line downlight aluminium round adjustable silver brushed

Technical drawing




Light distribution

Additional product photos




Logistics data




Single packaging

Width	90 mm
Height	90 mm
Length	40 mm
Weight	0,06 kg



Bulk packaging

Quantity	100
Width	380 mm
Height	220 mm
Length	470 mm
Volume	0,039 m3
Weight	9 kg
Comments	



Europallet

Quantity	2800
Height	1760 mm
Quantity in layer	400
Number of layers	8
Bulk quantity	3200
Weight	288 kg

---

LED line PRIME

Code: 244810

EAN: 5901583244810

**LED line downlight aluminium round  
adjustable silver brushed**

---

**Example application**