

LED line LITE


Code: 210035

EAN: 5905378210035

**DOWNLIGHT EASY FLEX 3CCT(3K/4K/5K)
70W 6300lm round IP20 White LITE**



EASY FLEX is a modern LED luminaire that combines innovative design, functionality, and flexible installation in one compact form. Available variants ranging from 6 to 70 W guarantee complete flexibility — an ideal solution for any renovation project, regardless of scale or requirements! The EASY FLEX family offers a luminous flux of up to 6300 lm and adjustable color temperature in three variants: 3000K, 4000K, and 5000K, allowing perfect adaptation of light to the character of the space.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	E
Warranty	3
Power	• 70 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 3000 K • 4000 K • 5000 K
Colour of the light	CCT
Colour rendering index Ra	80
IP protection rating	IP20
IK protection rating	05
IEC protection class	II
Luminous efficacy	90
Luminous flux	6300
The lumen maintenance factor	96
Lifetime L70B50	30 000 h
Colour consistency in McAdam ellipses	≤6

Parameter	Value
Frequency of the supply voltage	50/60Hz
Beam angle	120
LED type	SMD2835
LED quantity	248
Power Factor	>=0,9
Number of on/off cycles	15000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷40
Installation method	3in1 surface mounted, flush mounted, suspended
Mounting hole diameter	65-240
Height	28 mm
Fixture's diameter	750 mm
Weight	3,86
Colour	White


LED line LITE

Code: 210035

EAN: 5905378210035

**DOWNLIGHT EASY FLEX 3CCT(3K/4K/5K)
70W 6300lm round IP20 White LITE**

Technical drawing



Light distribution

Additional product photos




Logistics data



Single packaging

Width	35 mm
Height	755 mm
Length	755 mm
Weight	4,74 kg



Bulk packaging

Quantity	5
Width	195 mm
Height	775 mm
Length	775 mm
Weight	22 kg



Europallet

Quantity	60
Height	1,6 m
Bulk quantity	12
Weight	290 kg

LED line LITE

Code: 210035

EAN: 5905378210035

**DOWNLIGHT EASY FLEX 3CCT(3K/4K/5K)
70W 6300lm round IP20 White LITE**

Example application