

LED line PRIME

Code: 204225

EAN: 5905378204225

LED line PRIME FUSION linear lamp  
60W 4000K 7800lm 30\*90° white



FUSION linear setting of the LED line PRIME with 60W and 4000K colour temperature provides a light stream of 7800 lm, perfectly dispersed in the corner 30x90°. Made of aluminum, it is characterized by excellent heat discharge, which translates into a long life. Protection class IP20 and IK08 guarantee durability. The luminous efficiency is 130 lm/W and the colour mapping coefficient Ra = 80.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	C
Warranty	5
Power	• 60 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IK protection rating	08
IEC protection class	I
Luminous efficacy	130
Luminous flux	7800
The lumen maintenance factor	96
Lifetime L70B50	50 000 h

Parameter	Value
Survival factor	0.9
Colour consistency in McAdam ellipses	≤6
Sling length	200 cm
Standby power	0
Mounting type	mixed
Frequency of the supply voltage	50/60Hz
Power Factor	0.9
Lamp's warm-up time to 60%	1 s
Ambient temperature suitable for operation	-20÷45
For indoor use	Inside
Length	1444
Width	70
Height	52

LED line PRIME

Code: 204225

EAN: 5905378204225


LED line PRIME FUSION linear lamp  
60W 4000K 7800lm 30\*90° white

Technical drawing

Light distribution


Additional product photos

Logistics data




Single packaging

Width	1444 mm
Height	52 mm
Length	70 mm
Weight	1,97 kg



Bulk packaging

Quantity	12
Width	1550 mm
Height	260 mm
Length	260 mm
Volume	0,104 m3
Weight	23,89 kg
Comments	



Europallet

Quantity	144
Height	1550 mm
Quantity in layer	144
Number of layers	1
Bulk quantity	144
Weight	286,8 kg

---

LED line PRIME

Code: 204225

EAN: 5905378204225

**LED line PRIME FUSION linear lamp  
60W 4000K 7800lm 30\*90° white**

---

**Example application**