

LED line LITE


Code: 203280

EAN: 5905378203280

**LUMINO Floodlight 4000K 10W 1000lm
120° IP65 LITE**



LED LUMINO 10W from LED line LITE is an advanced light source with a luminous flux of 1000 lm. It is characterized by the colour of light 4000 K, which provides natural and pleasant lighting. Made of aluminium casting and tempered glass, it guarantees high durability and resistance to atmospheric conditions thanks to IP65 leak class.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	F
Warranty	3
Power	• 10 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	70
IP protection rating	IP65
IK protection rating	05
IEC protection class	I
Luminous efficacy	100
Luminous flux	1000
The lumen maintenance factor	96
Lifetime L70B50	25 000 h
Survival factor	0.9

Parameter	Value
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
Beam angle	110
LED type	SMD LED
LED quantity	15
Power Factor	0,9
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Length	92
Width	104
Height	21
Weight	160
Material (housing)	Die cast aluminium
Material (cover)	Tempered glass


LED line LITE

Code: 203280


EAN: 5905378203280

**LUMINO Floodlight 4000K 10W 1000lm
120° IP65 LITE**

Technical drawing






Light distribution



Additional product photos



Logistics data



Single packaging

Quantity	1
Width	92 mm
Height	21 mm
Length	104 mm
Weight	0,14 kg

Bulk packaging

Quantity	40
Width	240 mm
Height	220 mm
Length	285 mm
Volume	0,015 m3
Weight	5,95 kg

Europallet

Height	1760 mm
Quantity in layer	480
Number of layers	8
Bulk quantity	3840
Weight	571,2 kg

LED line LITE

Code: 203280

EAN: 5905378203280

**LUMINO Floodlight 4000K 10W 1000lm
120° IP65 LITE**

Example application