

LED line PRIME

Code: 210745

EAN: 5905378210745

**Power supply for 3 phase rail
LUMICANTO right white PRIME**

Current connection to LUMICANTO rail right white PRIME is a modern solution with high functionality. It is characterized by working voltage 220-240V AC and rated current 16A, which ensures efficiency and safety of use. The plastic casing guarantees durability and the protection class against electrical shock I increases the safety level of the installation.



Technical data

Parameter	Value
Warranty	5/7*
IEC protection class	I
Rated power	220-240V AC
Rated current	16A
Mounting type	3 phase rail
Frequency of the supply voltage	50/60Hz
Ambient temperature suitable for operation	5÷40

Parameter	Value
Length	98
Width	32
Height	32
Power supply connection	tak
Equivalent	XTS 11
Colour	White
Material (housing)	Plastic

LED line PRIME

Code: 210745

EAN: 5905378210745

**Power supply for 3 phase rail
LUMICANTO right white PRIME**

Technical drawing

Light distribution

Additional product photos




Logistics data




Single packaging

Width	30 mm
Height	100 mm
Length	30 mm
Weight	0,06 kg



Bulk packaging

Quantity	100
Width	300 mm
Height	300 mm
Length	300 mm
Volume	0,027 m ³
Weight	5,6 kg



Europallet

Height	1800 mm
Quantity in layer	800
Number of layers	6
Bulk quantity	4800
Weight	268,8 kg

LED line PRIME

Code: 210745

EAN: 5905378210745

**Power supply for 3 phase rail
LUMICANTO right white PRIME**

Example application