MORE EFFICIENCY FOR THE LED WORLD

LE D line

LED line PRIME

LED line PRIME FUSION linear lamp 20W 4000K 2600lm 0-10V 90*110° white


Code: 204065

EAN: 5905378204065

A C

The FUSION 20W linear luminaire from the PRIME LED line is an advanced lighting solution, which, emitting a light stream of 2600 Im, provides a bright and uniform light with a colour temperature of 4000 K. Thanks to the 0-10V dimming technology used and a high light efficiency of 130 Im/W, the device adapts effectively to different arrangements.





CE

Technical c	lata
-------------	------

Parameter	Value
Energy efficiency class 2019/2015	С
Warranty	5
Power	• 20 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IK protection rating	08
IEC protection class	I
Luminous efficacy	130
Luminous flux	2600
The lumen maintenance factor	96
Lifetime L70B50	50 000 h

Parameter	Value
Survival factor	0.9
Dimmable function	O-10
Colour consistency in McAdam ellipses	≤6
Sling length	200 cm
Standby power	0
Mounting type	mixed
Frequency of the supply voltage	50/60Hz
Power Factor	0,9
Lamp's warm-up time to 60%	ls
Ambient temperature suitable for operation	-20÷45
For indoor use	Inside
Length	586
Width	70
Height	52

MORE EFFICIENCY FOR THE LED WORLD



LED line PRIME

Code: 204065

Light distribution

EAN: 5905378204065

LED line PRIME FUSION linear lamp 20W 4000K 2600lm 0-10V 90*110° white

Technical drawing


Additional product photos








Logistics data




Single packaging

Width	586 mm
Height	52 mm
Length	70 mm
Weight	1,14 kg



Bulk packaging

Quantity	12
Width	690 mm
Height	260 mm
Length	260 mm
Volume	0,046 m3
Weight	13,93 kg
Comments	



Europallet

	202
Quantity	288
Height	1710 mm
Quantity in layer	48
Number of layers	6
Bulk quantity	288
Weight	672 kg

MORE EFFICIENCY FOR THE LED WORLD



LED line PRIME

Code: 204065

EAN: 5905378204065

LED line PRIME FUSION linear lamp 20W 4000K 2600lm 0-10V 90*110° white

Example application