

LED line PRIME

Code: LL-60-24

EAN: 5905378200166

Power Supply 60-24 IP67 60W 24V
PRIME

The PRIME 60-24 IP67 LED line power supply is an efficient power supply with 60W and 24V output voltage. The operating area includes an input voltage range of 90 to 264V AC and a frequency of 47 to 63Hz. IP67 protection class provides high resistance to moisture and dust, making it ideal for applications in difficult conditions. The power factor PF is 0.95 and the efficiency reaches 0.84.



5
WARRANTY

IP
67

PF
0,95

24V
DC

MAX
 -30÷70°C

Technical data

Parameter	Value	Parameter	Value
Warranty	5	Insulation strength	3kVAC
Power	• 60 W	EMC standards	EN55015
Voltage	• 90-265 V AC	Mounting type	surface
IP protection rating	IP67	Inrush current (typ.)	70A/230VAC
IEC protection class	II	Power Factor	>=0,95
Output current range	0 ÷ 2.5	Ambient temperature suitable for operation	-30÷50
Input voltage frequency range	50 ÷ 60Hz	Length	165 mm
Rated current	0,275	Width	43 mm
Safety standards	IP67	Height	32 mm
Efficiency	0,84	Weight	0,4 kg
Voltage tolerance	-/+5.0%	Output voltage	• 24 V
Ambient humidity	20 ÷ 90%		


LED line PRIME

Code: LL-60-24

EAN: 5905378200166

Power Supply 60-24 IP67 60W 24V
PRIME

Technical drawing






Light distribution

Additional product photos



Logistics data



Single packaging

Quantity	1
Width	52 mm
Height	35 mm
Length	185 mm
Weight	0,43 kg

Bulk packaging

Quantity	40
Width	205 mm
Height	215 mm
Length	385 mm
Weight	17,5 kg

Europallet

Quantity	1920
Height	1,90 m
Quantity in layer	
Number of layers	
Bulk quantity	48
Weight	865 kg

LED line PRIME

Code: LL-60-24

EAN: 5905378200166

Power Supply 60-24 IP67 60W 24V
PRIME

Example application