

LED line PRIME

Code: 216792-II

EAN: 5905378228641

Road luminaire CAMINO 3CCT(3/4/5,7K)
70W 9800 lm IP66 grey PRIME



CAMINO CCT are fixtures designed for harsh weather conditions, **available in three power variants: 50W, 70W, 100W, 150W**. Equipped with carefully selected and quality-tested components, they ensure **reliability of operation** and a long lifespan of the fixtures



Technical data

Parameter	Value
Energy efficiency class 2019/2015	C
Warranty	5/7*
Power	70 W
Voltage	220-240 V AC
Correlated colour temperature	3000 K 4000 K 5700 K
Colour of the light	CCT
Colour rendering index Ra	70
IP protection rating	IP66
IK protection rating	08
IEC protection class	I
Luminous efficacy	140
Luminous flux	9800 lm
The lumen maintenance factor	96
Lifetime L70B50	100 000 h
L80B* – difference B10–B50 ≈ 1% (according to LightingEurope) – negligible	75000 h
L90B* – difference B10–B50 ≈ 1% (according to LightingEurope) – negligible	50000 h

Parameter	Value
Survival factor	0.9
Frequency of the supply voltage	50/60Hz
Beam angle	150 x 110
LED type	LUMILEDS 2835
LED quantity	96
Power Factor	0,95
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-40÷50
For indoor use	Outside
Length	520 mm
Width	200 mm
Height	92 mm
Weight	2,5 kg
Material (housing)	Die cast aluminium
Material (cover)	Tempered glass


LED line PRIME

Code: 216792-II

EAN: 5905378228641

Road luminaire CAMINO 3CCT(3/4/5,7K)
70W 9800 lm IP66 grey PRIME

Technical drawing






Light distribution

Additional product photos



Logistics data



Single packaging

Width	514 mm
Height	80 mm
Length	200 mm
Weight	2,9 kg

Bulk packaging

Quantity	1
Width	560 mm
Height	116 mm
Length	236 mm
Volume	
Weight	2,9 kg

Europallet

Quantity	90
Height	1840 mm
Number of layers	1
Bulk quantity	90
Weight	300 kg

LED line PRIME

Code: 216792-II

EAN: 5905378228641

**Road luminaire CAMINO 3CCT(3/4/5,7K)
70W 9800 lm IP66 grey PRIME**

Example application

