

LED line PRIME Code: 470942 EAN: 5907777470942

LED line High-Bay UFO 150W 130lm/W 4000K 60° RAIDER 130





The LED RAIDER 130 with a power of 150 W provides exceptional light parameters with 130 lm/W capacity and a total light stream of 19 500 lumens. Its neutral light color (4000 K) guarantees natural color reproduction, and the 60° distribution angle allows precise lighting of selected areas. Aluminium casing and polycarbonate canister provide durability and resistance to atmospheric conditions, as confirmed by IP65 and IK08 leak classes.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	E
Energy class	A+
Warranty	5
Power	• 150 W
Voltage	• 100-277 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IK protection rating	08
IEC protection class	1
Luminous efficacy	130
Luminous flux	19500
The lumen maintenance factor	96
Lifetime L70B50	50 000 h
Survival factor	0.9

Parameter	Value
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
Fixture's diameter	250 mm
Beam angle	60
LED type	SMD3030
LED quantity	200
Lifespan	100 000 h
Power Factor	0,95
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-40÷45
Height	191
Colour	Black
Material (housing)	Aluminium
Material (cover)	Polycarbonate




LED line PRIME Code: 470942 EAN: 5907777470942

LED line High-Bay UFO 150W 130lm/W 4000K 60° RAIDER 130


Technical drawing

Light distribution

Luminous [cd/klm]




Additional product photos








Logistics data






Quantity	1
Width	330 mm
Height	330 mm
Length	200 mm
Weight	2,49 kg



Bulk packaging

Quantity	1
Width	330 mm
Height	330 mm
Length	200 mm
Volume	0,021 m3
Weight	0 kg
Comments	



Europallet

Quantity	48
Height	1650 mm
Quantity in layer	12
Number of layers	5
Bulk quantity	60
Weight	25 kg

MORE EFFICIENCY FOR THE LED WORLD



LED line PRIME Code: 470942 EAN: 5907777470942

LED line High-Bay UFO 150W 130lm/W 4000K 60° RAIDER 130

Example application