

LED line PRIME Code: 202122 EAN: 5905378202122

LED line PRIME Downlight CALMOS 18W 4000K 2100lm IP44





LED line setting PRime DOWNLIGHT CALMOS 18W is a modern solution that combines high quality performance with aesthetics. It is characterized by a brightness of 2100 lm and a neutral colour temperature of 4000 K, providing comfortable lighting. Thanks to IP44 leak class, the model is resistant to moisture, making it a versatile choice for various rooms. Aluminium casing and polycarbonate canister guarantee durability and longevity of the product.













Technical data

Parameter	Value
Energy efficiency class 2019/2015	E
Warranty	5
Power	• 18 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP44
IK protection rating	04
IEC protection class	II


Parameter	Value
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
LED type	SMD LED
Lamp's warm-up time to 60%	1
For indoor use	Inside
Installation method	recessed
Mounting hole diameter	220-240V AC
Colour	White
Material (housing)	Aluminium
Material (cover)	Polycarbonate



LED line PRIME Code: 202122 EAN: 5905378202122


LED line PRIME Downlight CALMOS 18W 4000K 2100lm IP44

Technical drawing



Light distribution

Luminous [cd/klm]



Additional product photos












Logistics data







Single packaging

Width		
Height		
Length		
Weight	0,3 kg	

Bulk packaging

Quantity	20
Width	420 mm
Height	410 mm
Length	450 mm
Volume	
Weight	6,35 kg

Europallet

Height	
Quantity in layer	
Number of layers	
Bulk quantity	
Weight	



LED line PRIME Code: 202122 EAN: 5905378202122

LED line PRIME Downlight CALMOS 18W 4000K 2100lm IP44

Example application

