

LED line LITE

Code: 206960

EAN: 5905378206960

LED line LITE Road luminaire FLAMINGO
30W 4000K 3000lm with twilight
sensor grey



FLAMINGO 30W 4000K is a modern lighting element, providing a light stream of 3,000 lumens. It is characterized by energy efficiency class E and high resistance to atmospheric factors due to IP65 leak class. The integrated dusk sensor automatically activates the setting at 50 lux and shuts down at 500 lux.

3
WARRANTY

IP
65

IK
08

PF
0,9

220-240V
AC

Technical data

Parameter	Value	Parameter	Value
Energy efficiency class 2019/2015	E	Mounting type	mixed
Warranty	3	Frequency of the supply voltage	50/60Hz
Power	• 30 W	Beam angle	140 x 70
Voltage	• 220-240 V AC	Sensor type	Crepuscular
Correlated colour temperature	• 4000 K	LED type	SMD LED
Colour of the light	White	LED quantity	48
Colour rendering index Ra	80	Power Factor	0,9
IEC protection class	I	Lamp's warm-up time to 60%	1 s
Luminous flux	3000	Ambient temperature suitable for operation	-25÷50
The lumen maintenance factor	96	Length	424
Lifetime L70B50	25 000 h	Width	89
Survival factor	0.9	Height	108
Colour consistency in McAdam ellipses	≤6	Weight	550
ULOR	0 %	Colour	Grey
Wyniki tłumaczenia Functional description of the daylight sensor [LUX]	50 lx: ON, 500 lx: OFF	Material (cover)	polycarbonate
Wire length	300 mm		

LED line LITE

Code: 206960

EAN: 5905378206960

LED line LITE Road luminaire FLAMINGO
30W 4000K 3000lm with twilight
sensor grey


Technical drawing

Light distribution

Additional product photos




Logistics data




Single packaging

Quantity	1
Width	424 mm
Height	108 mm
Length	89 mm
Weight	0,7 kg



Bulk packaging

Quantity	20
Width	450 mm
Height	430 mm
Length	470 mm
Volume	0,090 m3
Weight	14,35 kg



Europallet

Height	1800 mm
Quantity in layer	40
Number of layers	4
Bulk quantity	160
Weight	114,8 kg

LED line LITE

Code: 206960

EAN: 5905378206960

**LED line LITE Road luminaire FLAMINGO
30W 4000K 3000lm with twilight
sensor grey**

Example application