

LED line PRIME Code: 211315 EAN: 5905378211315

SUNSTREET 100W 6500K 750lm IP54 PRIME



New

SUNSTREET 100W 6500K is an innovative LED lamp with a power of 100 W, generating a light stream of 750 lm. It is characterized by white light at 6500 K, which provides bright and natural lighting. Thanks to IP54 leak class, the product displays high resistance to dust and moisture, ideal for external applications. The polycarbonate housing guarantees durability and the L70B50 life of 35,000 hours proves the long life of the lamp.













Technical data

Parameter	Value
Warranty	5
Power	• 100 W
Correlated colour temperature	• 6500 K
Colour of the light	White
Colour rendering index Ra	70
IP protection rating	IP54
Luminous flux	750
Lifetime L70B50	35 000 h
Loading time	3 h
Photo cell power	8
Photo cell voltage	5
Photo cell current	1,13
Photo cell width	210
Photo cell height	300
Mounting type	Lighting pole ø 60mm


Parameter	Value
Type of battery	LiFe Po4 3560mah
Beam angle	90
Sensor type	PIR
LED type	SMD LED 5050
LED quantity	56
Ambient temperature suitable for operation	-40~50
Installation method	Lighting pole/wall
Length	413
Width	231
Height	47
Weight	2,15 kg
	13
Material (housing)	ABS
Material (cover)	polycarbonate



LED line PRIME Code: 211315 EAN: 5905378211315

SUNSTREET 100W 6500K 750lm IP54 PRIME

Technical drawing



Light distribution

Additional product photos












Logistics data







Single packaging

Width	432 mm
Height	80 mm
Length	400 mm
Weight	2,2 kg

Bulk packaging

Quantity	5
Width	425 mm
Height	420 mm
Length	447 mm
Weight	13,9 kg

Europallet

Height	1950 mm
Bulk quantity	40
Weight	120 kg



LED line PRIME Code: 211315 EAN: 5905378211315

SUNSTREET 100W 6500K 750lm IP54 PRIME

Example application

