

LED line LITE

Code: 205598-AW3HAT

EAN: 5905378216693

Panel Backlit 2in1 40W 4000K 4000LM
62x62 white emergency module 3h
autotest LITE



The 40W Backlit Panel 2in1 emitting white light with temperature of 4000K provides excellent lighting thanks to a light stream of 4000 lumens. The panel dimensions are standard 62x62 cm design, ideal for different interiors. Equipped with an emergency module with up to three hours working time, it provides reliability in emergency situations.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	E
Warranty	2
Power	<ul style="list-style-type: none">40 W
Voltage	<ul style="list-style-type: none">220-240 V AC
Correlated colour temperature	<ul style="list-style-type: none">4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IK protection rating	02
IEC protection class	I
Luminous efficacy	100
Luminous flux	4000
The lumen maintenance factor	96

Parameter	Value
Lifetime L70B50	30 000 h
Survival factor	0.9
Dimmable function	PWM
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
Beam angle	120
Power Factor	0,9
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Height	38
Material (housing)	Metal
Material (cover)	Polystyrene

LED line LITE

Code: 205598-AW3HAT

EAN: 5905378216693

Panel Backlit 2in1 40W 4000K 4000LM
62x62 white emergency module 3h
autotest LITE


Technical drawing

Light distribution


Additional product photos




Logistics data



Single packaging



Bulk packaging



Europallet

Quantity

LED line LITE

Code: 205598-AW3HAT

EAN: 5905378216693

**Panel Backlit 2in1 40W 4000K 4000LM
62x62 white emergency module 3h
autotest LITE**

Example application