

LED line LITE

Code: 211612-II


EAN: 5905378220126

LINIX 4000K 45W 5400lm IP65 150cm gray LITE



LINIX LITE is a modern LED fixture with high energy efficiency and durability. With a luminous efficacy of 120 lm/W and a wide beam angle of 120° it provides even and comfortable lighting. The built-in microwave motion sensor (30lx; 30 sec.; 4m; 120°) allows for light control only when needed,

The fixtures can be connected into continuous light lines - up to 12 fixtures, allowing for flexible adaptation of lighting to large spaces. With easy installation and solid construction, LINIX LITE is an excellent choice for demanding users.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	D
Warranty	3
Power	• 45 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
IP protection rating	IP65
IEC protection class	II
Luminous efficacy	120
Luminous flux	5400
Lifetime L70B50	20 000 h
Standby power	0
Mounting type	surface

Parameter	Value
Frequency of the supply voltage	50/60Hz
CRI colour rendering index	80
Beam angle	120
Power Factor	0,95
Ambient temperature suitable for operation	-20/+40
Length	1563 mm
Width	53 mm
Height	35 mm
Weight	0,35 kg
Colour	White
Material (housing)	Polycarbonate
Material (cover)	Polystyrene


LED line LITE

Code: 211612-II

EAN: 5905378220126

**LINIX 4000K 45W 5400lm IP65 150cm
gray LITE**

Technical drawing




Light distribution

Additional product photos



Logistics data



Single packaging

Quantity	
Width	51 mm
Height	25 mm
Length	1575 mm
Weight	0,363 kg

Bulk packaging

Width	275 mm
Height	230 mm
Length	1580 mm
Weight	11,9 kg
Comments	

Europallet

Quantity	360
Height	1900 mm
Quantity in layer	12
Number of layers	1
Bulk quantity	12
Weight	180 kg

LED line LITE

Code: 211612-II

EAN: 5905378220126

**LINIX 4000K 45W 5400lm IP65 150cm
gray LITE**

Example application

